

# MIPS Reference Data

①



## CORE INSTRUCTION SET

NAME, MNEMONIC	FOR-MAT	OPERATION (in Verilog)	OPCODE / FUNCT (Hex)
<b>Add</b>	<b>add</b>	<b>R R[rd] = R[rs] + R[rt]</b>	<b>(1) 0 / 20<sub>hex</sub></b>
Add Immediate	addi	I R[rt] = R[rs] + SignExtImm	(1,2) 8 <sub>hex</sub>
Add Imm. Unsigned	addiu	I R[rt] = R[rs] + SignExtImm	(2) 9 <sub>hex</sub>
Add Unsigned	addu	R R[rd] = R[rs] + R[rt]	0 / 21 <sub>hex</sub>
And	and	R R[rd] = R[rs] & R[rt]	0 / 24 <sub>hex</sub>
And Immediate	andi	I R[rt] = R[rs] & ZeroExtImm	(3) c <sub>hex</sub>
Branch On Equal	beq	I if(R[rs]==R[rt]) PC=PC+4+BranchAddr	(4) 4 <sub>hex</sub>
Branch On Not Equal	bne	I if(R[rs]!=R[rt]) PC=PC+4+BranchAddr	(4) 5 <sub>hex</sub>
Jump	j	J PC=JumpAddr	(5) 2 <sub>hex</sub>
Jump And Link	jal	J R[31]=PC+8;PC=JumpAddr	(5) 3 <sub>hex</sub>
Jump Register	jr	R PC=R[rs]	0 / 08 <sub>hex</sub>
Load Byte Unsigned	lbu	I R[rt]={24'b0,M[R[rs] +SignExtImm](7:0)}	(2) 24 <sub>hex</sub>
Load Halfword Unsigned	lhu	I R[rt]={16'b0,M[R[rs] +SignExtImm](15:0)}	(2) 25 <sub>hex</sub>
Load Linked	ll	I R[rt] = M[R[rs]+SignExtImm]	(2,7) 30 <sub>hex</sub>
Load Upper Imm.	lui	I R[rt] = {imm, 16'b0}	f <sub>hex</sub>
Load Word	lw	I <b>R[rt] = M[R[rs]+SignExtImm]</b>	(2) <b>23<sub>hex</sub></b>
Nor	nor	R R[rd] = ~ (R[rs]   R[rt])	0 / 27 <sub>hex</sub>
Or	or	R R[rd] = R[rs]   R[rt]	0 / 25 <sub>hex</sub>
Or Immediate	ori	I R[rt] = R[rs]   ZeroExtImm	(3) d <sub>hex</sub>
Set Less Than	slt	R R[rd] = (R[rs] < R[rt]) ? 1 : 0	0 / 2a <sub>hex</sub>
Set Less Than Imm.	slti	I R[rt] = (R[rs] < SignExtImm) ? 1 : 0	(2) a <sub>hex</sub>
Set Less Than Imm. Unsigned	sltiu	I R[rt] = (R[rs] < SignExtImm) ? 1 : 0	(2,6) b <sub>hex</sub>
Set Less Than Unsig.	sltu	R R[rd] = (R[rs] < R[rt]) ? 1 : 0	(6) 0 / 2b <sub>hex</sub>
Shift Left Logical	sll	R R[rd] = R[rt] << shamt	0 / 00 <sub>hex</sub>

## ARITHMETIC CORE INSTRUCTION SET

②

NAME, MNEMONIC	FOR-MAT	OPERATION	OPCODE / FUNCT (Hex)
Branch On FP True	bc1t	FI if(FPcond)PC=PC+4+BranchAddr	(4) 11/8/1--
Branch On FP False	bc1f	FI if(!FPcond)PC=PC+4+BranchAddr	(4) 11/8/0/--
Divide	div	R Lo=R[rs]/R[rt]; Hi=R[rs]%R[rt]	0/--/--1a
Divide Unsigned	divu	R Lo=R[rs]/R[rt]; Hi=R[rs]%R[rt]	(6) 0/--/--1b
FP Add Single	add.s	FR F[fd] = F[fs] + F[ft]	11/10/--/0
FP Add Double	add.d	FR {F[fd],F[fd+1]} = {F[fs],F[fs+1]} + {F[ft],F[ft+1]}	11/11/--/0
FP Compare Single	c.x.s*	FR FPcond = (F[fs] op F[ft]) ? 1 : 0	11/10/--/y
FP Compare Double	c.x.d*	FR FPcond = ({F[fs],F[fs+1]} op {F[ft],F[ft+1]}) ? 1 : 0	11/11/--/y
		* (x is eq, lt, or le) (op is ==, <, or <=) (y is 32, 3c, or 3e)	
FP Divide Single	div.s	FR F[fd] = F[fs] / F[ft]	11/10/--/3
FP Divide Double	div.d	FR {F[fd],F[fd+1]} = {F[fs],F[fs+1]} / {F[ft],F[ft+1]}	11/11/--/3
FP Multiply Single	mul.s	FR F[fd] = F[fs] * F[ft]	11/10/--/2
FP Multiply Double	mul.d	FR {F[fd],F[fd+1]} = {F[fs],F[fs+1]} * {F[ft],F[ft+1]}	11/11/--/2
FP Subtract Single	sub.s	FR F[fd]=F[fs] - F[ft]	11/10/--/1
FP Subtract Double	sub.d	FR {F[fd],F[fd+1]} = {F[fs],F[fs+1]} - {F[ft],F[ft+1]}	11/11/--/1
Load FP Single	lwc1	I F[rt]=M[R[rs]+SignExtImm]	(2) 31/--/--/0
Load FP Double	ldc1	I F[rt]=M[R[rs]+SignExtImm]; F[rt+1]=M[R[rs]+SignExtImm+4]	(2) 35/--/--/0
Move From Hi	mghi	R R[rd] = Hi	0 / --/--/10
Move From Lo	mflr	R R[rd] = Lo	0 / --/--/12
Move From Control	mfc0	R R[rd] = CR[rs]	10 / 0/--/0
Multiply	mult	R {Hi,Lo} = R[rs] * R[rt]	0/--/--/18
Multiply Unsigned	multu	R {Hi,Lo} = R[rs] * R[rt]	(6) 0/--/--/19
Shift Right Arith.	sra	R R[rd] = R[rt] >> shamt	0/--/--/3
Store FP Single	swc1	I M[R[rs]+SignExtImm] = F[rt]	(2) 39/--/--/0
Store FP Double	sdc1	I M[R[rs]+SignExtImm] = F[rt]; M[R[rs]+SignExtImm+4] = F[rt+1]	(2) 3d/--/--/0

## FLOATING-POINT INSTRUCTION FORMATS

FR	opcode	fmt	ft	fs	fd	funct
	31	26 25	21 20	16 15	11 10	6 5
						0
FI	opcode	fmt	ft	immediate		
	31	26 25	21 20	16 15		

Set Less Than Imm.	slt	I	$R[rt] = (R[rs] < \text{SignExtImm}) ? 1 : 0$	(2)	$a_{\text{hex}}$
Set Less Than Imm. Unsigned	sltiu	I	$R[rt] = (R[rs] < \text{SignExtImm}) ? 1 : 0$	(2,6)	$b_{\text{hex}}$
Set Less Than Unsig.	sltu	R	$R[rd] = (R[rs] < R[rt]) ? 1 : 0$	(6)	$0 / 2b_{\text{hex}}$
Shift Left Logical	sll	R	$R[rd] = R[rt] \ll \text{shamt}$		$0 / 00_{\text{hex}}$
Shift Right Logical	srl	R	$R[rd] = R[rt] \gg \text{shamt}$		$0 / 02_{\text{hex}}$
Store Byte	sb	I	$M[R[rs] + \text{SignExtImm}](7:0) = R[rt](7:0)$	(2)	$28_{\text{hex}}$
Store Conditional	sc	I	$M[R[rs] + \text{SignExtImm}] = R[rt];$ $R[rt] = (\text{atomic}) ? 1 : 0$	(2,7)	$38_{\text{hex}}$
Store Halfword	sh	I	$M[R[rs] + \text{SignExtImm}](15:0) = R[rt](15:0)$	(2)	$29_{\text{hex}}$
Store Word	sw	I	$M[R[rs] + \text{SignExtImm}] = R[rt]$	(2)	$2b_{\text{hex}}$
Subtract	sub	R	$R[rd] = R[rs] - R[rt]$	(1)	$0 / 22_{\text{hex}}$
Subtract Unsigned	subu	R	$R[rd] = R[rs] - R[rt]$		$0 / 23_{\text{hex}}$

(1) May cause overflow exception  
(2)  $\text{SignExtImm} = \{ 16\{\text{immediate}[15]\}, \text{immediate} \}$   
(3)  $\text{ZeroExtImm} = \{ 16\{1b'0\}, \text{immediate} \}$   
(4)  $\text{BranchAddr} = \{ 14\{\text{immediate}[15]\}, \text{immediate}, 2'b0 \}$   
(5)  $\text{JumpAddr} = \{ \text{PC} + 4[31:28], \text{address}, 2'b0 \}$   
(6) Operands considered unsigned numbers (vs. 2's comp.)  
(7) Atomic test&set pair;  $R[rt] = 1$  if pair atomic, 0 if not atomic

### BASIC INSTRUCTION FORMATS

<b>R</b>	opcode	rs	rt	rd	shamt	funct
	31 26 25	21 20	16 15	11 10	6 5	0
<b>I</b>	opcode	rs	rt	immediate		
	31 26 25	21 20	16 15	0		
<b>J</b>	opcode	address				
	31 26 25	0				

### FLOATING-POINT INSTRUCTION FORMATS

<b>FR</b>	opcode	fmt	ft	fs	fd	funct
	31 26 25	21 20	16 15	11 10	6 5	0
<b>FI</b>	opcode	fmt	ft	immediate		
	31 26 25	21 20	16 15	0		

### PSEUDOINSTRUCTION SET

NAME	MNEMONIC	OPERATION
Branch Less Than	blt	if( $R[rs] < R[rt]$ ) PC = Label
Branch Greater Than	bgt	if( $R[rs] > R[rt]$ ) PC = Label
Branch Less Than or Equal	btle	if( $R[rs] \leq R[rt]$ ) PC = Label
Branch Greater Than or Equal	bge	if( $R[rs] \geq R[rt]$ ) PC = Label
Load Immediate	li	$R[rd] = \text{immediate}$
Move	move	$R[rd] = R[rs]$

### REGISTER NAME, NUMBER, USE, CALL CONVENTION

NAME	NUMBER	USE	PRESERVED ACROSS A CALL?
\$zero	0	The Constant Value 0	N.A.
\$at	1	Assembler Temporary	No
\$v0-\$v1	2-3	Values for Function Results and Expression Evaluation	No
\$a0-\$a3	4-7	Arguments	No
\$t0-\$t7	8-15	Temporaries	No
\$s0-\$s7	16-23	Saved Temporaries	Yes
\$t8-\$t9	24-25	Temporaries	No
\$k0-\$k1	26-27	Reserved for OS Kernel	No
\$gp	28	Global Pointer	Yes
\$sp	29	Stack Pointer	Yes
\$fp	30	Frame Pointer	Yes
\$ra	31	Return Address	Yes

③

**OPCODES, BASE CONVERSION, ASCII SYMBOLS**

MIPS opcode (31:26)	(1) MIPS funct (5:0)	(2) MIPS funct (5:0)	Binary	Decimal	Hexa-decimal	ASCII Character	Decimal	Hexa-decimal	ASCII Character
(1)	sll	add.f	00 0000	0	0	NUL	64	40	@
		sub.f	00 0001	1	1	SOH	65	41	A
j	srl	mul.f	00 0010	2	2	STX	66	42	B
jal	sra	div.f	00 0011	3	3	ETX	67	43	C
beq	sllv	sqrt.f	00 0100	4	4	EOT	68	44	D
bne		abs.f	00 0101	5	5	ENQ	69	45	E
blez	srlv	mov.f	00 0110	6	6	ACK	70	46	F
bgtz	srav	neg.f	00 0111	7	7	BEL	71	47	G
addi	jr		00 1000	8	8	BS	72	48	H
addiu	jalr		00 1001	9	9	HT	73	49	I
slti	movz		00 1010	10	a	LF	74	4a	J
sltiu	movn		00 1011	11	b	VT	75	4b	K
andi	syscall	round.w.f	00 1100	12	c	FF	76	4c	L
ori	break	trunc.w.f	00 1101	13	d	CR	77	4d	M
xori		ceil.w.f	00 1110	14	e	SO	78	4e	N
lui	sync	floor.w.f	00 1111	15	f	SI	79	4f	O
(2)	mfhi		01 0000	16	10	DLE	80	50	P
	mthi		01 0001	17	11	DC1	81	51	Q
	mflo	movz.f	01 0010	18	12	DC2	82	52	R
	mtlo	movn.f	01 0011	19	13	DC3	83	53	S
			01 0100	20	14	DC4	84	54	T
			01 0101	21	15	NAK	85	55	U
			01 0110	22	16	SYN	86	56	V
			01 0111	23	17	ETB	87	57	W
	mult		01 1000	24	18	CAN	88	58	X
	multu		01 1001	25	19	EM	89	59	Y
	div		01 1010	26	1a	SUB	90	5a	Z
	divu		01 1011	27	1b	ESC	91	5b	[
			01 1100	28	1c	FS	92	5c	\
			01 1101	29	1d	GS	93	5d	]
			01 1110	30	1e	RS	94	5e	^
			01 1111	31	1f	US	95	5f	_
lb	add	cvt.s.f	10 0000	32	20	Space	96	60	·
lh	addu	cvt.d.f	10 0001	33	21	!	97	61	a
lwl	sub		10 0010	34	22	"	98	62	b
lw	subu		10 0011	35	23	#	99	63	c

**IEEE 754 FLOATING-POINT STANDARD**

④

**IEEE 754 Symbols**


Exponent	Fraction	Object
0	0	± 0
0	≠0	± Denorm
1 to MAX - 1	anything	± Fl. Pt. Num.
MAX	0	±∞
MAX	≠0	NaN

$(-1)^S \times (1 + \text{Fraction}) \times 2^{(\text{Exponent} - \text{Bias})}$


where Single Precision Bias = 127,  
Double Precision Bias = 1023.

S.P. MAX = 255, D.P. MAX = 2047


**IEEE Single Precision and Double Precision Formats:**




**MEMORY ALLOCATION**



**STACK FRAME**



**DATA ALIGNMENT**




Value of three least significant bits of byte address (Big Endian)

lbu	and	cvt.wf	10 0100	36	24	\$	100	64	d
lhu	or		10 0101	37	25	%	101	65	e
lwr	xor		10 0110	38	26	&	102	66	f
	nor		10 0111	39	27	'	103	67	g
sb			10 1000	40	28	(	104	68	h
sh			10 1001	41	29	)	105	69	i
swl	slt		10 1010	42	2a	*	106	6a	j
sw	sltu		10 1011	43	2b	+	107	6b	k
			10 1100	44	2c	,	108	6c	l
			10 1101	45	2d	-	109	6d	m
swr			10 1110	46	2e	.	110	6e	n
cache			10 1111	47	2f	/	111	6f	o
ll	tge	c.f.f	11 0000	48	30	0	112	70	p
lwc1	tgeu	c.un.f	11 0001	49	31	1	113	71	q
lwc2	tlt	c.eq.f	11 0010	50	32	2	114	72	r
pref	tltu	c.ueq.f	11 0011	51	33	3	115	73	s
	teq	c.olt.f	11 0100	52	34	4	116	74	t
ldc1		c.ult.f	11 0101	53	35	5	117	75	u
ldc2	tne	c.ole.f	11 0110	54	36	6	118	76	v
		c.u.le.f	11 0111	55	37	7	119	77	w
sc		c.sf.f	11 1000	56	38	8	120	78	x
swc1		c.ngle.f	11 1001	57	39	9	121	79	y
swc2		c.seq.f	11 1010	58	3a	:	122	7a	z
		c.ngl.f	11 1011	59	3b	;	123	7b	{
		c.lt.f	11 1100	60	3c	<	124	7c	
sdc1		c.nge.f	11 1101	61	3d	=	125	7d	}
sdc2		c.le.f	11 1110	62	3e	>	126	7e	~
		c.ngt.f	11 1111	63	3f	?	127	7f	DEL

(1) opcode(31:26) == 0

(2) opcode(31:26) == 17<sub>ten</sub> (11<sub>hex</sub>); if fmt(25:21) == 16<sub>ten</sub> (10<sub>hex</sub>) f = s (single);  
if fmt(25:21) == 17<sub>ten</sub> (11<sub>hex</sub>) f = d (double)

## EXCEPTION CONTROL REGISTERS: CAUSE AND STATUS



BD = Branch Delay, UM = User Mode, EL = Exception Level, IE = Interrupt Enable

## EXCEPTION CODES

Number	Name	Cause of Exception	Number	Name	Cause of Exception
0	Int	Interrupt (hardware)	9	Bp	Breakpoint Exception
4	AdEL	Address Error Exception (load or instruction fetch)	10	RI	Reserved Instruction Exception
5	AdES	Address Error Exception (store)	11	CpU	Coprocessor Unimplemented
6	IBE	Bus Error on Instruction Fetch	12	Ov	Arithmetic Overflow Exception
7	DBE	Bus Error on Load or Store	13	Tr	Trap
8	Sys	Syscall Exception	15	FPE	Floating Point Exception

## SIZE PREFIXES (10<sup>x</sup> for Disk, Communication; 2<sup>x</sup> for Memory)

SIZE	PRE-FIX	SIZE	PRE-FIX	SIZE	PRE-FIX	SIZE	PRE-FIX
10 <sup>3</sup> , 2 <sup>10</sup>	Kilo-	10 <sup>15</sup> , 2 <sup>50</sup>	Peta-	10 <sup>-3</sup>	milli-	10 <sup>-15</sup>	femto-
10 <sup>6</sup> , 2 <sup>20</sup>	Mega-	10 <sup>18</sup> , 2 <sup>60</sup>	Exa-	10 <sup>-6</sup>	micro-	10 <sup>-18</sup>	atto-
10 <sup>9</sup> , 2 <sup>30</sup>	Giga-	10 <sup>21</sup> , 2 <sup>70</sup>	Zetta-	10 <sup>-9</sup>	nano-	10 <sup>-21</sup>	zepto-
10 <sup>12</sup> , 2 <sup>40</sup>	Tera-	10 <sup>24</sup> , 2 <sup>80</sup>	Yotta-	10 <sup>-12</sup>	pico-	10 <sup>-24</sup>	yocto-

The symbol for each prefix is just its first letter, except  $\mu$  is used for micro.